

# DM 6010 P

## DCS 6000 Delegate Unit w/Fixed Mic 15.8 in. (40 cm)



### Configuration

DM 6010 P

The DM 6010 P is a fully digital, portable delegate unit perfectly suited for permanent meeting rooms or temporary discussion-style meetings. The unit features a built-in loudspeaker and a fixed 15.8 in. (40 cm) gooseneck microphone with illuminated red ring to indicate microphone ON status.

Each unit enables participants to speak, register a request-to-speak and listen to other speakers. The unit can either be controlled by the microphone button or remotely by the operator/conference chair. The gain/sensitivity of the microphone/loudspeaker can be remotely controlled by the operator. The microphone button is surrounded with an LED to indicate whether the unit is on (RED) or in the request-to-speak queue (GREEN). The loudspeaker is automatically switched off to prevent acoustic feedback when the microphone is active. The units can be easily daisy chained with shielded FTP or STP Cat-5e cables (sold separately).

### Highlights

- Excellent sound quality.
- Cost-effective structured Cat-5e cabling.
- No pick-up of mechanical table noise thru proprietary double rubber band capsule suspension.
- Remote microphone gain adjustment.
- Elegant, unobtrusive, black units.

### Requires

#### Requires a cable.

EC 6000-0.5  
EC 6000-01  
EC 6000-02  
EC 6000-03  
EC 6000-05  
EC 6000-10  
EC 6000-20  
EC 6000-30  
EC 6000-50

### Used With

CU 6005	CM 6060 F
CU 6011	DM 6510 F
EX 6010	DM 6560 F
AO 6004	CM 6660 F
AO 6008	FD 4010 FHB-4432-GB-100
PS 6000	FC 4010 FHB-4432-GB-100
RP 6004	FD 4011 FHB-4432-GB-100
JB 6002	FC 4011 FHB-4432-GB-100
JB 6004	FD 6012 FHB-6033-GB-100
DM 6010 P	MU 6040 D
DM 6060 P	MU 6040 C
DM 6070 P	MU 6042 D
CM 6070 P	DV 6501 F
DM 6090 P	CS 6032 FHB1
CM 6090 P	IS 6132 P
DC 6990 P	CO RJ45 F
AM 6040	CO RJ45 M-5.2
DM 6060 F	

### Includes

DM 6010 P

Specifications		DM 6010 P
Audio	Loudspeaker Frequency Response	150 Hz - 15 kHz
	Loudspeaker diameter	3 in. (76 mm)
	Loudspeaker maximum power	3 W RMS
	Microphone Frequency Response	100 Hz - 15 kHz
	Microphone Sensitivity	-22 dBv/Pa
	Microphone Max SPL	125 dB (3% THD)
	Microphone equivalent noise	Approx. 20 dB SPL
	Microphone Front/Back ratio	>20 dB (1 kHz)
Controls & Indicators	Microphone Button	Red/ Green illuminating LED; red indicates microphone is active, green indicates request-to-speak.
	Illuminated Microphone Ring	Ring around the microphone head that illuminates bright red when the microphone is on.
Interconnections	DCS-LAN	Two (2) RJ45 ports, screened with auto-termination
Power	Power Consumption	2.4 Watts
Physical	Dimensions (H x W x D)	2.40 x 5.91 x 6.61 in. (61 x 150 x 168 mm)
	Microphone length	15.8 in. (40 cm)
	Color	black
	Unit Weight	2.0 lbs. (0.90 kg)
	Shipping Weight	3.0 lbs. (1.36 kg)
	Mounting	Tabletop (portable or semi-flush mounted)

## FAQ's

- Q** Do I need software to use the voting feature?  
**A** Software is required to handle the voting, results, display etc.
- Q** How many microphone units can be connected to the CU?  
**A** The total number of units that can be connected is based on cable length, type of CU and the type of unit being connected, but on each output of a CU 6010 you can typically get about 30 to 42 delegate/chairman units, or 20 to 30 flush mount units, or 16 Interpreter Sets. More units can be added with extension power supplies. Contact Listen Technical Support for more information.
- Q** How far can the daisy chain cabling go?  
**A** 200 meters without any repeaters. Up to 640 meters with repeaters and further when using optical cables. Contact Listen tech support for more information.
- Q** Can I mix and match different microphone styles with the system?  
**A** Yes, all the DCS 6000 units with a loop through (all except the DT/IT) can be connected in parallel or serial configurations.
- Q** Is the cabling proprietary cabling?  
**A** No, but it must be shielded Cat-5 (FTP/STP). Depending on the specification, higher shielded CAT cables can be used for extension cables as well.
- Q** Can I use a conference system without chairman unit?  
**A** Yes you can, however, there will not be any priority function available. The chairman will not be able to manage the microphone system.
- Q** How many microphones can be connected to the CU 6005?  
**A** 50 without a license, 500 with a license and additional CUs.